



Provisional

E24065

LINEAR LOW DENSITY POLYETHYLENE Extrusion Coating

E24065 is a Butene Co-monomer based Linear Low Density Polyethylene (LLDPE) and designed for extrusion coating applications in blends with LDPE.

TYPICAL CHARACTERISTICS*

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE
Density (23°C)	ASTM D 1505	g/cc	0.924
Melt Flow Index (190°C / 2.16 Kg)	ASTM D 1238	g/10 min.	6.5
Film properties **			
Ultimate tensile strength (MD/TD)	ASTM D 882	MPa	25/20
Elongation at Break (MD/TD)	ASTM D 882	%	20
Tensile strength at Yield	ASTM D 882	Мра	12 / 11.5
Co-efficient of Friction: Static / Dynamic	ASTM D 1894		0.79 / 0.69

^{*} Typical characteristics and not to be taken as specifications

APPLICATIONS:

Coating on Woven fabric etc

Regulatory Information

For various regulatory and food contact certifications / declarations please contact RIL representative.

Storage Recommendations

• Bags should be stored in dry/closed conditions at temperatures below 50°C and protected from UV / direct sunlight.

Reliance Industries Limited, Product Application & Research Center (PARC)
RIL Baroda Complex, P. O. Petrochemicals, Vadodara 391346, Gujrat. Tel.: +91-265-6696000. E-mail: polymer_patsupport@ril.com Website: www.ril.com

The information and data presented herein is true and accurate to the best of our knowledge. No warranty or guarantee expressed or implied, is made regarding performance or other wise. This information and data may not be considered as a suggestion to use our products without taking into account existing patents, or legal provisions or regulations, whether national or international. • The user of any information and/or data is advised to obtain the latest details from any of the offices of the company or its authorised agents, as the information and/or data is subject to change based on the research and development work undertaken by the company.

^{**}Typical Values with 40 micron film made with 1.8mm die gap & 2.25 BUR